

METALLIC WAX

Metallic Wax for decorative surfaces

DESCRIPTION

Isoplam[®] Metallic Wax is a self-shining product that creates a protective film for concrete decorative surfaces, keeping them unaltered in time. Its water-based formulation allows its use also in cycles where solvent-free products are required.

Isoplam[®] Metallic Wax perfectly adheres on the support on which it is applied and it does not peel.

FIELDS OF USE

Isoplam[®] Metallic Wax can be used for the protection of decorative surfaces, such as:

- Microoverlay[®] surfaces;
- acidified and "nuvolato" floorings;
- resin floorings;
- floorings treated with Plam Densifier, for its correct maintenance;
- rubber, pvc and linoleum floorings.

APPLICATION AND MAINTENANCE

Surfaces must be accurately cleaned. There must not be oil or grease stains. Contact our technicians in order to find the right products to properly clean the support.

We do not suggest the use of Isoplam[®] Metallic Wax of a very light or very dark colour if the surface is exposed to the sun; in this case, use Isoplam[®] Plam Opaque.

Isoplam[®] Metallic Wax has to be applied with an Isoplam[®] Wax Spreader in two thin and crossed coats (wait at least one hour between one coat and the other). The product in excess could cause the whitening of the surface.

Clean the tools simply with water and soap.

Decorative surfaces treated with Isoplam[®] Metallic Wax can be kept unaltered and brilliant in time using Isoplam[®] Wax Clean for the ordinary cleaning.

Isoplam[®] Metallic Wax can be removed with Isoplam[®] Wax Remover.

This product makes surfaces slipping: do not apply it outdoor, in wet places or places affected by water stagnation.

TECHNICAL FEATURES

ASPECT	Milky liquid
SOLUBILITY	in water
FLASH POINT	non-flammable
BOILING POINT	>100° C

PERFORMANCE

1 Lt of product is enough for 18-20 m² (two coats).

PACKAGES AND STORAGE

Isoplam[®] Metallic Wax is supplied in packages of 5 Lt or 20 Lt.

If kept in its original packaging and at temperatures between 5 and 35 ° C, the product will be kept for more than 1 year from the date shown on the package (the batch number indicates, year after week, the day).

SAFETY

Consult the Safety Data Sheet before use. Isoplam[®] Metallic Wax is intended for professional use only.

IMPORTANT:

The product METALLIC WAX is intended for the use as indicated above. Adding any other product will impair the final result. All information contained herein is based on the best practical experiences and laboratory research. It is the customer's responsibility to determine whether the product is suitable for the intended application. The manufacturer declines all responsibility on the results due to incorrect application of its products. The product shall always be tested on a small area before full scale application. This data sheet replaces all previous data sheets. ISOPLAM reserves the right to change the data on the data sheet at any time. METALLIC WAX is intended for professional use only. ISOPLAM provides frequent and on demand trainings for its customers. The use of ISOPLAM products without receiving the proper certification will be at the customer's own risk.